

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.


Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

Your **competition** just filed
a **patent application.**



[Log Out](#)
[Order Form](#)
[Work Files](#)
[View Cart](#)

[ABOUT DELPHION](#)
[PRODUCTS](#)
[NEWS & EVENTS](#)
[MY ACCOUNT](#)
[IP SEARCH](#)
[HELP](#)

[Browse Codes](#)
[IP Listings](#)
[Prior Art](#)
[Derwent](#)
[Advanced](#)
[Boolean](#)
[Quick/Number](#)

The Delphion
Integrated
View

Other Views:
[INPADOC](#)

Title: **JP8241709A2: MANUFACTURE OF NEGATIVE ELECTRODE OF NONAQUEOUS ELECTROLYTE BATTERY**

► [Want to see a more descriptive title highlighting what's new about this invention?](#)

Country: **JP** Japan
Kind: **A**

Inventor(s): **NISHIMURA WASUKE**
TAKAHASHI RYUJI
OO FUMIO

Applicant/Assignee: **MATSUSHITA ELECTRIC IND CO LTD**



[News, Profiles, Stocks and More about this company](#)

Issued/Filed Dates: **Sept. 17, 1996 / March 7, 1995**

Application Number: **JP1995000046966**

IPC Class: **H01M 4/12; H01M 4/04; H01M 6/02; H01M 6/16; H01M 10/40;**

Priority Number(s): **March 7, 1995 JP1995000046966**

Abstract:



Purpose: To manufacture the negative electrode without adhering lithium to the pressurizing surface of a pressurizing die at the time of manufacturing the negative electrode of a nonaqueous electrolyte battery by pressing a rectangular piece of lithium metal with a die having the specified pressurizing surface.


Constitution: A rectangular piece of lithium metal or lithium alloy is inserted into a negative electrode can or a lower die having the circular inner bottom surface. This rectangular piece is pressed by a die having the pressurizing surface, in which at least a part is formed into the rough surface, and having the material film having the excellent sliding property in relation to the lithium metal or lithium alloy in the rough surface of the pressurizing surface, and the rectangular piece is pressurized for deformation. In the case where the abutment area of the die is assumed at 100, the area of the rough surface at 65 or more is necessary. Shape of the die is formed into the concentric circular shape, spiral shape, radial shape, or random pattern having a groove at 0.02-0.30mm of depth. As the material film having the excellent sliding property, for example, the film made of liquid paraffin, fluoride group surface active agent, or Lewis base type organic solvent is used.

COPYRIGHT: (C)1996,JPO

► [See a clear and precise summary of the whole patent, in understandable terms.](#)

Family: [Show known family members](#)

Other Abstract Info: **CHEMABS 125(26)334207T CAN125(26)334207T DERABS C96-474126**



View
Image

1 page

DERC96-474126

Foreign References: No patents reference this one



Nominate this
for the Gallery...

[Subscribe](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [FAQ](#) | [Site Map](#) | [Help](#) | [Contact Us](#)

© 1997 - 2002 Delphion Inc.



(19)

(11) Publication number: **08241709 A**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **07046966**(51) Intl. Cl.: **H01M 4/12 H01M 4/04 H01M 6/02 H01M 6/16 H01M 10/40**(22) Application date: **07.03.95**

(30) Priority:

(43) Date of application
publication: **17.09.96**(84) Designated contracting
states:(71) Applicant: **MATSUSHITA ELECTRIC IND CO
LTD**(72) Inventor: **NISHIMURA WASUKE
TAKAHASHI RYUJI
OO FUMIO**

(74) Representative:

**(54) MANUFACTURE OF
NEGATIVE ELECTRODE OF
NONAQUEOUS
ELECTROLYTE BATTERY**

(57) Abstract:

PURPOSE: To manufacture the negative electrode without adhering lithium to the pressurizing surface of a pressurizing die at the time of manufacturing the negative electrode of a nonaqueous electrolyte battery by pressing a rectangular piece of lithium metal with a die having the specified pressurizing surface.

CONSTITUTION: A rectangular piece of lithium metal or lithium alloy is inserted into a negative electrode can or a lower die having the circular inner bottom surface. This rectangular piece is pressed by a die having the pressurizing surface, in which at least a part is formed into the rough surface, and having the material film having the excellent sliding property in relation to the lithium metal or lithium alloy in the rough surface of the pressurizing surface, and the rectangular piece is pressurized for

deformation. In the case where the abutment area of the die is assumed at 100, the area of the rough surface at 65 or more is necessary. Shape of the die is formed into the concentric circular shape, spiral shape, radial shape, or random pattern having a groove at 0.02-0.30mm of depth. As the material film having the excellent sliding property, for example, the film made of liquid paraffin, fluoride group surface active agent, or Lewis base type organic solvent is used.

COPYRIGHT: (C)1996,JPO